
Model: CUE-180-VG


Direct Drive Upblast Centrifugal Roof Exhaust Fan



Dimensional	
Quantity	8
Weight w/o Acc's (lb)	89
Weight w/ Acc's (lb)	91
Standard Curb Cap Size (in.)	30 x 30
Roof Opening (in.)	26.5 x 26.5

OVERALL HEIGHT MAY BE GREATER DEPENDING ON MOTOR, ADAPTER, AND/OR HINGE BASE.

Performance	
Requested Volume (CFM)	2,600
Actual Volume (CFM)	2,600
Total External SP (in. wg)	0
Fan RPM	688
Operating Power (hp)	0.15
Elevation (ft)	5,138
Airstream Temp.(F)	70
Air Density (lb/ft3)	0.062
Tip Speed (ft/min)	3,333
Static Eff. (%)	0



pipsa.com.mx

Misc Fan Data	
Fan Energy Index (FEI)	-
Outlet Velocity (ft/min)	890

Motor	
Motor Mounted	Yes
Size (hp)	3/4
Voltage/Cycle/Phase	115/60/1
Enclosure	ODP
Motor RPM	875
Efficiency Rating	High
Windings	1
FLA (Amps)	8.8
Min. Circuit Ampacity (MCA)	11
Max. Overcurrent Protection (MOP)	20
Short Circuit Current Rtg (SCCR)	5 kA

Sound Power by Octave Band

Sound Data	62.5	125	250	500	1000	2000	4000	8000	LwA	dBA	Sones
Inlet	70	76	69	63	62	62	50	40	69	57	8.3

Notes:

All dimensions shown are in units of in.
*NEC FLA, MCA and MOP are for reference only – based on tables 430.248 or 430.25 of National Electric Code 2020. Actual motor FLA may vary, for sizing thermal overload, consult factory. MCA and MOP values shown only account for the motor, not accessories (damper actuator, field supplied VFD, etc).
LwA - A weighted sound power level, based on ANSI S1.4
dBA - A weighted sound pressure level, based on 11.5 dB attenuation per Octave band at 5 ft - dBA levels are not licensed by AMCA International
Sones - calculated using ANSI/AMCA 301 at 5 ft

Model: CUE-180-VG

Direct Drive Upblast Centrifugal Roof Exhaust Fan

Standard Construction Features:

- Aluminum housing - Backward curved composite (sizes 60-95) or aluminum (sizes 99-300) wheel - Aluminum curb cap with prepunched mounting holes - Drain trough - Ball bearing motors (sizes 85-300 and all Vari Green), sleeve bearing motors (sizes 60-80) - Motor isolated on shock mounts - Corrosion resistant fasteners - Removable power pack - Tool-less hood entry

Selected Options & Accessories:

Motor - Vari-Green EC motor
Control - Dial for balancing
Standard Curb Cap Size - 30 Square
UL/cUL 705 Listed - "Power Ventilators"
Switch, NEMA-1, Toggle,
Junction Box Mounted & Wired in weather-protected motor compartment
Aluminum Wheel Material
Conduit Chase Qty 1
Unit Warranty: 1 Yr (Standard)

The Vari-Green Motor included in this order has a 'Multi-Voltage' ability. The red wire on the motor is called a 'Voltage Doubler', and when it is connected the motor can be powered by 115V.
If the Red wire is disconnected, then the motor can be powered with 208-230/277V. The motor will leave the factory with the voltage doubler wired per the order.

pipsa.com.mx

Vari-Green
Motor & Control Options


An EC motor that uses AC input power and internally converts it to DC power. Potentiometer (dial) mounted on the motor enclosure adjusts the speed (RPM) down 80%. Vari-Green motors feature a soft-start and inherent thermal and current protection built into each unit. Inrush current at start up is eliminated and the motor will automatically reduce speed or turn off if overloaded or it becomes too hot.

Motor Configuration

Input Voltage:	115
Speed Reference:	Dial on Motor
Permanent Dial:	Yes

Control Configuration

Control Type:	Dial on Motor
Transformer:	None



pipsa.com.mx