-GENESIS-

Riser Rated Security & Control Cable
Part Number: 2214

18 AWG 2 Stranded Conductors Shielded

Ratings	CMR, CL3R, FPLR, FT4, Sunlight Resistant
Approvals	ETL Listed

Construction

Conductor	18 AWG 19 Strand Bare Copper
Conductor Count	2
Insulation	Polypropylene (0.006" nom.)
Insulation Colors	Black, Red
Lay Length	2.50" nom.
Shielding	Aluminum Foil/Mylar w/ 24 AWG Tinned-Copper Drain
Rip Cord	Yes
Jacket	PVC (0.015 " nom.)
Overall Diameter	0.154" nom.
Print Legend	GENESIS P/N 2214 2C 18AWG SHIELDED 3038058 (ETL) CL3R OR FPLR OR CMR C(ETL)US FT4 SUN RES 75C (RoHS) W/O# XXXXXX-XXXXXXX XXXXFT A B C D E F 1 2 3 4 5 6 7 8 9

pipsa.com.mx

Properties

Operating Voltage	300 Volts max.
DC Resistance	6.66 Ohms/1000' at 20°C
Capacitance	42.9 pF/ft. nom.
Impedance	36 Ohms nom.
Temperature	-20°C to 75°C
Flame Rating	UL 1666 (Riser); CSA C22.2 No. 2556 (FT4)
RoHS Compliant	Yes
Country of Origin	USA

Published: 2018-10-19